

MP9 Controller

The MP9 is custom tailored for QSR's Server based applications, DineTime Host client for Windows, and DineTime GuestView software. The MP9 offers flexible connectivity to fit your restaurant needs from the back office to the restaurant floor, and everywhere in between.



FEATURE	SPECIFICATION
Operating System	Microsoft Windows Embedded Standard 7E
Processor	Intel® Core™, i3-4330T, 3.5 GHz 4 MB cache, 2 cores, 4 threads
Chipset	Intel® Q87 Express
Memory Options	4GB DDR3
Storage	500 GB 7200 rpm HDD
Graphic Options	Intel® HD Graphics 4600 Up to 1920x1080 VGA Up to 2560x1600 Display Port
Networking	Intel® I217LM Gigabit Network Connection (standard), Optional Wireless - Intel® Wireless-N 7260 802.11 M.2 a/b/g/n NIC Card
I/O Ports	6 USB 3.0 1 Display Port 1 VGA 1DB9 1 RJ-45 1 3.5 mm Microphone Jack 1 3.5 mm Audio Output
Boot Options	Hard Drive, External USB
Dimensions	1.3" x 7.0" x 6.9" (H x W x D)
Weight	2.9 lbs.
Power	Power Surge and Overvoltage Protection External Switching Power Supply Input: 100-240 VAC, 50-60 Hz Output: 9 VDC, 2.0A Regulated
Environmental	5° – 55° Celsius
Certifications	FCC Part 15, Class A, EN55022 (1944) Class A, EU ROHS, CE, WEEE, NOM, KCC, BSMI, C-Tick, VCCI, Postel
Warranty	Limited 3-Year Hardware Warranty